

# Military Loudspeaker MK-25

Military Loudspeaker. MIL-STD 810E Compliant

# MK-25

## Product Description:

Military loudspeaker MK-25 is a 3 inch direct radiator, dynamic, permanent magnet type loudspeaker housed in an impact-proof waterproof case and is resistant to weather, water immersion, humidity, temperature extremes, vibrations and bounce. Military loudspeaker MK-25 is intended for use with ground, airborne and seaborne service. Tactical equipment is mobile or fixed field communications equipment.

## Technical Characteristics:

Frequency Range : 300 Hz - 3500 Hz.  
Power Rating : 2 Watts RMS max.  
Input level : The input level for the following requirements is 0.05 - 3 V RMS.  
Impedance : The input impedance of the MK-25 is between 8000 Ohms.  
Supply DC: 10.5 - 12.5 V , 170 mA.

## MIL-STD Compliant:

Temperature operation/storage - MIL-STD 810E Compliant  
Vibration operation/storage - MIL-STD 810E Compliant  
Humidity operation/storage - MIL-STD 810E Compliant

## MIL-STD Connectors:

MIL-STD Compliant

## Temperature range for operation:

-25 to +55 C

## Temperature range for storage:

-40 to +85 C

## Dimensions:

118 mm x 73 mm x 110 mm.

## Net weight:

0.5 Kg



All right reserved (C) 1995-2007 Peryphon Ltd  
10 Hamelacha St., block 209, New Industrial Park Rosh-Ha'ayin 48091 Israel  
TEL: 972-3-9025682 FAX: 972-3-9025684 E-mail: peryphon@zahav.net.il

**PERYPHON LTD**  
[http:// www.peryphon.co.il](http://www.peryphon.co.il)