

Military loudspeaker TA-6090

8 W Military LAN VOIP and Analog Loudspeaker. MIL-STD 1275B /461C-D-E/810E Compliant



Product Description:
Military loudspeaker TA-6090 is a 6.5 inch direct radiator, dynamic, permanent magnet type loudspeaker, housed in a die cast metal enclosure and is resistant to weather, water immersion, humidity, temperature extremes, vibrations and bounce. It is intended for use with ground, airborne and seaborne service.
Tactical equipment is mobile or fixed field communications equipment.

Characteristics :

Analog or/and LAN VOIP inputs:

- 1 - Analog
- 2 -LAN 10/100/1000Mb (optional)

Frequency Range :

40 Hz-3000 Hz (300-3500 Hz -optional).

Power Rating :

4 Watts RMS (nominal) and
8 Watts RMS to peak.

Input level :

The input level for the following requirements is 10 mV- 3 V RMS,AGC system presents.

Impedance :

The input impedance of the TA-6090A/TA is between 1100 Ohms (analog).

Attenuation :

The TA-6090A/TA output is attenuated at no less than 40 dB when using the volume control.

Temperature :

-30 to + 70 C

Dimensions :

220 mm x 160 mm x 200 mm

Net weight :

5.1 kg.

MIL-STD Connectors: MIL-STD Compliant

Temperature operation/storage - MIL-STD 810E Compliant

Vibration operation/storage - MIL-STD 810E Compliant

Humidity operation/storage - MIL-STD 810E Compliant

Integrated power supply:

Voltage operation - 9...36 VDC - MIL-STD 704A-D/ MIL-STD 1275A-B /MIL-STD 461C-D-E Compliant



All right reserved. 1995-2008 © Peryphon Ltd ®
10 Hamelacha St., block 209, New Industrial Park Rosh-Ha'ayin 48091 Israel
TEL: 972-3-9025682 FAX: 972-3-9025684 E-mail: peryphon@zahav.net.il

TA-6090

PERYPHON LTD

[http:// www.peryphon.co.il](http://www.peryphon.co.il)