

# Military Rugged LAN Router Cisco 2811/ 2911

MIL-STD 810F Compliant.

# CISCO 2811/ 2911



The Military Rugged LAN Router Cisco 2811/ 2911 provides the following support:

- Wire-speed performance for concurrent services such as security and voice , and advanced services to multiple T1/E1/xDSL WAN rates
- Enhanced investment protection through increased performance and modularity
- Increased density through High-Speed WAN Interface Card Slots (four)
- Enhanced Network Module Slot
- Support for over 90 existing and new modules
- Support for majority of existing AIMs, NMs, WICs, VWICs, and VICs

Two Integrated 10/100 Fast Ethernet ports  
Optional Layer 2 switching support with Power over Ethernet (PoE) (as an option)

The Military Rugged LAN Router Cisco 2811/ 2911 provides the following Security support:

- On-board encryption
- Support of up to 1500 VPN tunnels with the AIM-EPII-PLUS Module
- Antivirus defense support through Network Admission Control (NAC)
- Intrusion Prevention as well as full Cisco IOS Firewall support and many more essential security features

The Military Rugged LAN Router Cisco 2811/ 2911 provides the following Voice support:

- Analog and digital voice call support
- Optional voice mail support
- Optional support for Cisco CallManager Express (Cisco CME) for local call processing in stand alone business for up to 36 IP Phones
- Optional support for Survivable Remote Site Telephony support for local call processing in small enterprise branch offices for up to 36 IP phones

The Military Rugged LAN Router Cisco 2811/ 2911 Router is MIL-STD Compliant:

- Temperature operation/storage - MIL-STD 810F Compliant
- Vibration operation/storage - MIL-STD 810F Compliant
- Humidity operation/storage - MIL-STD 810F Compliant
- Voltage operation - 18...75 VDC (+24V)
- Rugged LAN Switch WS-C375024TS MIL-STD Connectors:D38999
- LAN Connectors - MIL-STD Compliant D38999 III 24WB35BN
- Power Connector - MIL-STD Compliant D38999 III 24WB05PN K (A-B)

Rugged LAN Switch WS-C375024TS Physical and Environmental:

- Dimensions - 450 x 370 x 88.10mm
- Weight 8.7 kg
- Operation temperature range: -5 C.....+50 C



All right reserved (C) 1995-2010 Peryphon Ltd  
10 Hamelacha St., block 209, New Industrial Park Rosh-Ha'ayin 48091 Israel  
TEL: 972-3-9025682 FAX: 972-3-9025684 E-mail: peryphon@zahav.net.il

**PERYPHON LTD**  
[http:// www.peryphon.co.il](http://www.peryphon.co.il)